

ORBEA



ORCA M30.

ESTÁ EN ESTOS COLORES:



BLANCO-NEGRO-ROJO
(BRILLO)



NEGRO-ROJO
(SATINADO-BRILLO)



ANTRACITA-TURQUESA
(SATINADO)

ESPECIFICACIONES Y OPCIONES

CUADRO	Orbea Orca carbon OME, monocoque,tapered 1-1/8" - 1,5", PF 86mm, powermeter compatible, brake internal cable routing, EC/DC compatible, 130mm rear spacing, 27,2mm seat tube.
HORQUILLA	Orca OME carbon fork, full carbon steerer, tapered 1-1/8" - 1,5", carbon dropouts.
PLATO	Shimano 105 5800 34x50t
DIRECCION	FSA 1-1/8 - 1-1/2" Integrated Carbon Cup ACB Bearings
MANILLAR	FSA Omega Compact
POTENCIA	Orbea OC-II
MANETAS	Shimano 105 5800
FRENO	Shimano 105 5800
PIÑON	Shimano 105 5800 11-28t 11-Speed
CAMBIO	Shimano 105 5800
DESVIADOR	Shimano 105 5800
CADENA	Fsa Team Issue
RUEDA	Vision Team 30 Comp Clincher
CUBIERTA	Vittoria Rubino Foldable 700x25 60TPI G+
PEDALES	N/A
TIJA SILLIN	Orbea OC-II Carbon 27.2x350mm
SILLIN	Prologo K3 STN size 141 mm
CINTA MANILLAR	Bar Tape
	White Shock Proof

GEOMETRÍA

TALLA	47	49	51	53	55	57	60
1 - SEAT_TUBE	440	460	480	500	520	540	570
2 - TOP_TUBE	507	522	535	550	561	575	591
3 - HEAD_TUBE	110	125	140	155	175	200	220
4 - CHAIN_STAY				408			
5 - BB_HEIGHT	269,5	269,5	269,5	271,5	271,5	271,5	271,5
6 - BB_DROP	72	72	72	70	70	70	70
7 - WHEELBASE	972	977	983	983	991	1001	1015
8 - HEAD_ANGLE	71	71,5	72	72,8	73	73,2	73,2
9 - SEAT_ANGLE	74,5	74	73,7	73,5	73,5	72,3	72,3
10 - STANDOVER	738,5	755,59	773,35	793,2	812,79	831,48	857,84
11 - REACH	367	370	375	382	387	393	402
12 - STACK	515	530	547	564	584	603	627
13 - FORK_LENGTH				375			
14 - OFFSET	50	50	50	43	43	43	43

ERGONOMÍA

TALLA	BIELA	POTENCIA	MANILLAR
47	170	90	400
49	170	100	400
51	170	100	420
53	170	110	420
55	172.5	110	420
57	172.5	110	440
60	175	120	440

* La medida del manillar es centro-centro

